



Badger Meter Europa

Badger Meter Europa GmbH
Nürtinger Str. 76
72639 Neuffen (Germany)
Tel. +49-7025-9208-0
Fax +49-7025-9208-15
www.badgermeter.de
badger@badgermeter.de

Offering code

MID detector

MID electromagnetic flow meter

<u>Type</u>	
2	Type 2
3	Type 3
5	Type 5
6	Type 6
<u>Size DN 6 to DN 2000</u>	
<u>Pressure rate</u>	
<u>Process connections</u>	
F	DIN flanges
A	ANSI flanges
D	Threads acc. DIN 11851
T	TriClamps
W	Wafer
<u>Material</u>	
St	C-steel
V2	SST 1.4301 (ANSI 304)
V4	SST 1.4404 (ANSI 316)
<u>Liner</u>	
PT	PTFE
PFA	(DN 6-10)
HG	Hard rubber
WG	Soft rubber
HA	Halar
<u>Elektrodes</u>	
ML	Measure + empty pipe electrode
MEL	Measure + grounding + empty pipe electrode
<u>Electrode material</u>	
HC	Hastelloy C
TA	Tantalum
PG	Platinum/gold plated
PR	Platinum/Rhodium
<u>Housing</u>	
St	C-steel
V2	SST 1.4301 (ANSI 304)
V4	SST 1.4404 (ANSI 306)

MID - / - / - - / -

Example: MID 2 – 100 / 16 – F / St – HG – ML / HC - St

INQUIRY



MID amplifier

Amplifier

M10A	M1000 (92-275 VAC)
M10D	M1000 (9-36 VDC)
MB10A	M1000 blind version (VAC)
MB10D	M1000 blind version (VDC)
MBS10A	M1000 blind version, with stainless steel housing (VAC)
MBS10D	M1000 blind version, with stainless steel housing (VDC)
M20A	M2000 (85-265 VAC)
M20D	M2000 (9-36 VDC)
M30A	M3000 (85-265 VAC)
M30D	M3000 (24 VDC)
M40A	M4000 (85-265 VAC)
M40D	M4000 (24 VDC)
M50B0	M5000 (battery-operated/no battery pack)
M50B1	M5000 (battery-operated/1 battery pack)
M50B2	M5000 (battery-operated/2 battery packs)
M50AB	Line powered (battery back-up/100-240 VAC)
M50DB	(9-36 VDC)
	Mounted/remote/cable length
	M Amplifier detector mounted
	R Remote version cable length
	10 Remote amplifier with 10 m cable length
	15 Remote amplifier with 15 m cable length
	20 Remote amplifier with 20 m cable length
	25 Remote amplifier with 25 m cable length
	30 Remote amplifier with 30 m cable length

--	--	--

Example:

M10A	R
------	---

15

 m

Medium

Temperature

Application

Company

Contact person

Phone

Fax

E-mail

INQUIRY